

Technical Specifications for
Nedia S400

Nedia S400 is a 100% straw matrix stitch bonded between two light weight photodegradable nettings.

Index Value Properties:

Property	Test Method	Typical Value	
		English Units	Metric Units
Material composition	n/a	100% Straw	
Mass per unit area	ASTM D 6475	9 oz/sq.yd	305.1 oz/sq.m
Thickness	ASTM D 6525	0.32 inches	8.1 mm
Tensile Strength (MD x TD)	ASTM D 6818	169 x 107 lb/ft.	2.5 x 1.6 kN/m
Elongation (MD x TD)	ASTM D 6818	27.6 % x 29.4 %	
Light Penetration	ASTM D 6567	19%	
Water Absorption	ASTM D 1117	418%	
Manning's N	Observed	0.029	

Channel Performance Design Values*:

Property	Test Method	Typical Value	
		English Units	Metric Units
Unvegetated Shear Stress	ASTM D 6460	2.05 lb/sq. ft	98 Pa
Unvegetated Velocity	ASTM D 6460	9.3 ft./s	2.8 m/s
Vegetated Shear Stress	n/a	n/a	
Vegetated Velocity	n/a	n/a	

* Large scale results obtained by 3rd party GAI Accredited independent laboratory.

Standard Roll Sizes: 8' x 112.5' (2.44m x 34.3m) – 100 sy /roll



www.nedia.com



info@nedia.com